

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR- MA5003

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Heavy Duty Steel Doorset

Intended use:- 50mm thick Double leaf external pedestrian panic exit doorsets

Essential characteristics	Performance	Harmonised technical specification
Test report number: WIL329979 applies.		
Watertightness – Non-shielded (A)	NPD	EN 14351-1:2006 +A2:2016
Watertightness – Shielded (B)	NPD	
Dangerous substances	None	
Resistance to wind load – Test pressure	NPD	
Resistance to wind load – Frame deflection	NPD	
Load bearing capacity of safety devices	NPD	
Acoustic performance	NPD	
Thermal transmittance	2.0 W/m ² K	
Air Permeability	NPD	
Ability to Release	EN 1125, EN 179 & EN 1935	

Certificate of Constancy of Performance

2812-CPR- MA5003

Placed on the Market under the Name of

Doors4Security Ltd
Elizabeth Mill, Worrall Street, Congleton,
Cheshire, CW12 1DT, UK

and produced in the manufacturing plant

J/041 & E/393

This is coded format and the information is held by the Notified Body

This certificate attests that all provisions concerning the Assessment and Verification of Constancy of Performance described in Annex ZA of the standard(s):

EN 14351-1:2006 + A2:2016

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 10/12/2020 and will remain valid as long as neither the harmonised standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

Valid to: **03/11/2023**

ERO Project Reference: **EROWF10375**



Paul Duggan
Certification Manager

